

WATERPRISM: A Reinforcement-Learning Framework for Real-Time Flood, Drought, Water-Quality, and Geopolitical Water Security Risk Management

Unified Decision-Support Architecture, Empirical River Cam Catchment Validation, and Autonomous 5-D Infrastructure Control

Principal Investigator / Lead Architect: Harri Lanzett
Institutional Affiliation: Sampo AI Research Laboratory & Lansec Oy, Helsinki / Vantaa, Finland
Research Monograph Series: Sampo Deep-Tech Technical Report Series (WP-TR-2026-V1.0)
Compliance & Standards: ASME V&V 40 Computational Standard Aligned • EU WFD 2000/60/EC • UN/JRC GDACS Integrated

EXECUTIVE ABSTRACT & SYSTEM ARCHITECTURE

*This technical white paper investigates whether a single reinforcement-learning agent, trained across multiple hazard regimes, can coordinate flood, drought, and ecological water-quality risk management in real time from heterogeneous observational data streams — without requiring hazard-specific rule sets for each dimension. We present **WaterPrism**, an independent deep-tech decision-support platform evaluated and empirically validated on the River Cam catchment (Cambridge, UK) that addresses this challenge through four tightly coupled analytic layers: multi-source data fusion, predictive risk modelling, autonomous infrastructure control, and geopolitical water security intelligence.*

The data fusion layer applies Inverse-Distance-Weighted (IDW) spatial aggregation across nine heterogeneous gauge nodes sourced from the UK Environment Agency (EA) Flood Monitoring API and the Finnish Meteorological Institute (FMI) WFS, normalising precipitation, soil moisture, river stage, evapotranspiration, turbidity, and chlorophyll-a to a unified temporal grid against a bias-corrected ERA5 reanalysis baseline. Predictive risk is computed concurrently across flood (ERA5-analogue pattern matching yielding 48–168-hour lead-time forecasts), drought (composite 30-day precipitation anomaly, gauge percentiles, and FAO-56 Penman–Monteith evapotranspiration stress), and water quality (turbidity/chlorophyll-a proxies benchmarked against EU Water Framework Directive thresholds).

Autonomous infrastructure dispatch is governed by a Proximal Policy Optimisation (PPO) agent trained for 503,808 steps across 325 ERA5-augmented episodes (13 historical storm profiles × 25 what-if perturbations). The agent executes a continuous-discrete 5-dimensional action space spanning sluice-gate position, pump speed, pre-drain rate, flood barrier deployment, and evacuation advisory tier. Geopolitical water security intelligence is integrated via automated six-hour polling of the UN/JRC Global Disaster Alert and Coordination System (GDACS), monitoring six active strategic water-infrastructure threat nodes globally. Live empirical validation confirms physically consistent, cross-dimensional hazard response without state collapse.

4-Tier Risk Fusion Flood • Drought • Quality • Security	503,808 Steps PPO RL Policy Convergence	48–168 h Lead Time ERA5 Historical Storm Matching	5-D Actuator Dispatch Sluices • Pumps • Barriers • Alerts
---	---	---	---

1. The Multi-Hazard Challenge & System Overview

Modern water infrastructure management operates under compounding climatic and anthropogenic stress. Traditionally, municipal utilities, catchment authorities, and disaster response agencies employ isolated, hazard-specific decision-support systems. Flood management relies on hydraulic threshold alarms; drought mitigation is managed via retrospective reservoir depletion indices; and water-quality surveillance is dictated by periodic grab-sample laboratory telemetry. This structural fragmentation induces catastrophic blind spots at the intersections of hazard regimes:

- **The Drought-Quality Paradox:** Prolonged drought depletes baseline river discharge, drastically reducing natural effluent dilution capacity. Consequently, water quality decays precisely when volumetric water scarcity peaks.
- **The Storm-Runoff Conflict:** Intense convective storm events generate urban and agricultural runoff spikes, simultaneously maximizing flood crest risk and driving severe turbidity and nutrient shockloads that overwhelm treatment intakes.
- **Actuator Coupling Conflicts:** Autonomous or manual flood-prevention weir opening intended to prevent upstream inundation accelerates downstream toxic sediment scour, compromising regional potability and ecological compliance.

WaterPrism dissolves this hazard compartmentalization. Operating on a unified situational digital twin, the system continuously digests multi-source streaming hydrology, evaluates concurrent multi-dimensional risks, validates decisions against symbolic ethical boundaries, and dispatches coordinated 5-dimensional physical actions in real time.

2. High-Level Six-Pillar System Workflow

The WaterPrism architecture is structured into six synchronized operational roles that observe the exact same underlying state:

Pillar / Tab	Primary Operational Role	Underlying Analytical Mechanism
MONITOR	Situational Awareness & Geospatial Mapping	Real-time IDW spatial sensor fusion across UK EA & FMI gauge nodes; live basin choropleth; water-quality index mapping.
FORECAST	Predictive Early-Warning & Crisis Prioritization	ERA5-analogue storm matching (48–168 h lead time); FAO-56 Penman–Monteith drought trajectory; surge precursor tracking.
SCIENCE	Model Verification & Sensor Fusion Explainability	Numerical Weather Prediction (NWP) model comparison; gauge variance decomposition; epistemic uncertainty quantification.
GOVERNANCE	Symbolic Ethics & Regulatory Audit Trail	4-Agent Constitutional Ethics Validator; Gini inequality minimization ($G < 0.08$); SPHERE humanitarian standards; SHA-256 audit logs.
OPS	Infrastructure Health & Pump Optimization	Telemetry anomaly detection; pump duty cycle optimization; predictive weir maintenance; cavitation prevention.
SIMULATE	Historical Storm Replay & What-If Counterfactuals	Replay of 18 historical storm profiles (Harvey, Idalia, UK storms) with interactive barometric, wind, and soil-moisture overrides.

3. Multi-Source Observational Data Fusion Layer

A critical vulnerability of municipal water management is gauge heterogeneity and latency mismatch. WaterPrism resolves this via a real-time spatial aggregation pipeline that ingests, cleans, and harmonizes heterogeneous data streams onto a uniform spatio-temporal grid at 15-minute resolution.

Mathematical Formulation: Spatial IDW Aggregation

For any unmonitored catchment coordinate x , the estimated hydrometeorological state $u(x)$ is evaluated using a power-parameterized Inverse Distance Weighting (IDW, $p = 2$) kernel across N active gauge telemetry stations:

Equation 1 (Spatial Fusion Kernel):
$$u(\mathbf{x}) = \sum_{i=1}^N w_i(\mathbf{x}) \cdot u_i$$
where $w_i(\mathbf{x}) = d(\mathbf{x}, \mathbf{x}_i)^{-p} / \sum_{j=1}^N d(\mathbf{x}, \mathbf{x}_j)^{-p}$
where $d(\mathbf{x}, \mathbf{x}_i)$ denotes the Euclidean distance between target grid centroid $\mathbf{x}$ and gauge station $\mathbf{x}_i$, with singularity condition $u(\mathbf{x}) = u_i$ if $d(\mathbf{x}, \mathbf{x}_i) < \epsilon$ (10^{-5}).

Telemetry Station Network & Parameter Spectrum

The empirical prototype is validated on the River Cam catchment in Cambridgeshire, UK, supported by cross-regional calibration against high-latitude boreal data from the Finnish Meteorological Institute (FMI):

Station ID & Source	Monitored Telemetry Variables	Temporal Sampling & Latency	Analytical Weight in Fusion
E2043 (Cam-Baits Bite) UK Environment Agency	River stage (m), discharge (m ³ /s), velocity vector	15 min • REST API (< 60 s delay)	Primary Sluice Reference (0.35)
E2055 (Jesus Lock) UK Environment Agency	Upstream weir stage, gate aperture, bypass overflow	15 min • REST API (< 60 s delay)	Urban Flood Boundary (0.25)
E2114 (Bottisham Lock) UK Environment Agency	Downstream discharge, tailwater level, surge transit	15 min • REST API (< 60 s delay)	Drainage Sink Node (0.20)
FMI WFS (Boreal Sensor) Finnish Met. Institute	Precipitation intensity, soil moisture deficit, snow water eq.	10 min • WFS 2.0 GeoServer	Precipitation Driver (0.10)
ECMWF ERA5 Baseline Copernicus Climate Service	30-yr climatology, surface pressure, Penman–Monteith ET ₀	Hourly • Bias-Corrected Reanalysis	Climatological Prior (0.10)

4. Concurrent Predictive Risk Modelling Architecture

WaterPrism computes risk concurrently across three physical dimensions. Rather than collapsing indicators into a single obscure metric, each risk domain maintains an independent physical state engine:

A. Flood Risk Engine: ERA5-Analogue Pattern Matching

Instead of relying on slow hydrodynamic ODE grids during flash-flood crises, WaterPrism deploys an **ERA5-analogue pattern matching** engine over a curated library of 18 historical storm profiles (2005–2023). For the incoming meteorological precursor vector $x_t = [SLP, \Delta P_{3h}, WindSpeed, Precip_{24h}, SoilMoisture]$, the system evaluates normalized Euclidean distances against the historical manifold. When distance satisfies $D(x_t, x_{hist}) \leq 0.25$, historical hydrographs are warped to deliver rapid 48–168 hour lead-time stage forecasts with quantifiable confidence intervals.

B. Drought Risk Engine: Multi-Factor Climatological Depletion

Drought onset is calculated via a composite index uniting meteorological precipitation deficit, hydrologic baseflow depletion, and agronomic evaporative stress based on the standard FAO-56 Penman–Monteith equation:

Equation 2 (Composite Drought Index):
$$R_{Drought} = 0.40 \cdot I_{Anom}(P_{30d}) + 0.35 \cdot (1 - Q_{perc}) + 0.25 \cdot S_{ET0}$$

where I_{Anom} is the 30-day precipitation anomaly relative to the ERA5 1991–2020 climatological baseline, Q_{perc} is the EA gauge historical discharge percentile (0.0 to 1.0), and S_{ET0} is the standardized FAO-56 Penman–Monteith potential evapotranspiration stress coefficient.

C. Ecological Water Quality Engine: WFD Alignment

Water quality risk is continuously evaluated against European Union Water Framework Directive (WFD, 2000/60/EC) ecological reference thresholds. The engine fuses continuous turbidity (NTU), chlorophyll-a proxies (µg/L), and runoff spike coefficients:

WFD Ecological Status	Turbidity Range (NTU)	Chlorophyll-a (µg/L)	WaterPrism Operational Tier
HIGH Status	< 5.0 NTU	< 4.0 µg/L	Tier 0: Baseline Ecology Protected
GOOD Status	5.0 – 12.0 NTU	4.0 – 10.0 µg/L	Tier 1: Normal Municipal Supply Safe
MODERATE Status	12.0 – 25.0 NTU	10.0 – 25.0 µg/L	Tier 2: Advisory Watch • Aerator Armed
POOR Status	25.0 – 50.0 NTU	25.0 – 50.0 µg/L	Tier 3: Sluice Scour Interlock Active
BAD Status	> 50.0 NTU	> 50.0 µg/L	Tier 4: Intake Shutdown & Emergency Flush

5. Autonomous Reinforcement Learning Control Layer

To break the dependency on fragile, static rule-based threshold tables, WaterPrism deploys a continuous-control **Proximal Policy Optimisation (PPO)** reinforcement-learning agent (Schulman et al., 2017). The policy was trained for **503,808 simulation steps** across 325 ERA5-augmented episodes (comprising 13 historical storm profiles perturbed with 25 what-if parameter variations spanning barometric drop rate, wind speed, antecedent soil moisture, and tidal surge height).

State Space & 5-Dimensional Actuator Action Space

The agent operates over a 12-dimensional observation vector and outputs five simultaneous, coordinated physical control signals:

Dimension / Signal	Type & Range	Physical Actuator / Target Subsystem	Operational Objective
Action 1: Sluice Position	Continuous [0.0, 1.0]	Jesus Lock & Bottisham Lock Weir Gates	Regulates upstream river stage; prevents urban overtopping while dampening scour.
Action 2: Pump Speed	Continuous [0.0, 1.0]	Primary Station PS-CAM-001 (0–12 m³/s)	Dynamic evacuation of low-lying floodwaters with energy-optimal throttling.
Action 3: Pre-Drain Rate	Continuous [0.0, 1.0]	Retention Basins & Urban Storm Ponds	Proactive capacity clearance 12–24h prior to predicted convective rain peak.
Action 4: Barrier Deployment	Discrete {0, 1, 2}	Pneumatic Deployable Flood Defences	Deploys demountable barriers during surge alerts; prevents residential inundation.
Action 5: Advisory Tier	Discrete {0, 1, 2, 3}	Municipal SCADA & Public Warning API	Issues tiered flood/drought warnings to emergency services and utility managers.

Reward Function & Multi-Objective Loss

The PPO policy optimizes a composite reward R_{total} penalizing urban flood depths, pump energy consumption, and downstream sediment erosion, while rewarding drought storage retention:

Equation 3 (PPO Multi-Objective Reward):
$$R_t = -w_1 \cdot \max(0, h_t - h_{flood})^2 - w_2 \cdot E_{pump}(a_2) - w_3 \cdot \Delta Turbidity(a_1) + w_4 \cdot \min(V_t, V_{reserve})$$

Convergence achieved at mean episodic reward 27.265 (vs. baseline heuristic -14.82). Training executed with Stable Baselines3 across 325 parallelized vectorize environments.

6. Geopolitical Water Security & Global Threat Ingestion

Water security is no longer an isolated local meteorological problem; it is intrinsically linked to transnational supply chains, regional conflicts, and critical energy corridors. WaterPrism features a dedicated geopolitical threat tracking layer that continuously monitors six strategic water-infrastructure nodes while ingesting live disaster feeds globally:

Global Water Security Threat Matrix (Active Monitored Nodes)

Node ID & Location	Threat Category	Threat Classification	Operational Vulnerability & Impact Vector
WST-1: Gaza Catchment Eastern Mediterranean	Desalination Infrastructure Crisis	CRITICAL	97% coastal aquifer contamination; total dependency on compromised reverse-osmosis energy inputs; catastrophic public health risk.
WST-2: Red Sea Corridor Bab el-Mandeb Choke Point	Chemical Supply Corridor Risk	CRITICAL	Maritime interdiction threatens coagulant, chlorine, and membrane shipments necessary for Middle Eastern desalination.
WST-3: Yemen Coastal Zone Southern Red Sea	Desalination Plant Warfare	CRITICAL	Direct military targeting and sabotage of municipal water processing; water weaponization in civil conflict zones.
WST-4: Strait of Hormuz Persian Gulf	Intake Oil Slick Risk	HIGH	Naval military tensions risk crude tanker spills threatening intake channels that supply >80% of Gulf state municipal drinking water.
WST-5: Kakhovka / Dnipro Southern Ukraine	Dam Breach Legacy & Ecology	CRITICAL	Downstream toxic sediment flush, cooling water loss for Zaporizhzhia nuclear reactors, and catastrophic long-term agricultural canal loss.
WST-6: Gulf of Oman Indian Ocean Gateway	Tanker Transit Corridor	HIGH	Electronic warfare jamming of vessel navigation and water transport logistics supplying island utility hubs.

Automated GDACS & UNEP Feed Integration

Every six hours, WaterPrism automatically ingests the public-domain **UN/JRC Global Disaster Alert and Coordination System (GDACS)** RSS telemetry. The feed filters for Orange and Red alerts across drought, flood, and tropical cyclone events globally. During live operational validation (19 April 2026), 237 active items were processed, isolating 5 major international crisis vectors (including Tropical Cyclone SINLAKU-26 and four critical drought alerts spanning Southern Africa and the Andes), dynamically setting the global water-threat register to CRITICAL with 13 active events.

7. Symbolic Ethics Engine, Governance & SPHERE Auditing

A central requirement for municipal and utility deployment of autonomous AI is **provable governance**. Deep neural networks must never execute black-box physical actions (such as opening emergency flood barriers or shutting down municipal pumps) without passing through an explicit, machine-readable ethical boundary.

The 4-Agent Constitutional Ethics Validator

WaterPrism implements a four-agent consensus committee that reviews every PPO actuator recommendation before SCADA dispatch:

- Humanitarian Equity Agent (SPHERE Standards):** Verifies that no automated pump reduction or reservoir diversion drops community potable supply below the SPHERE Survival Minimum (15 L/capita/day).
- Ecological Compliance Agent (EU WFD):** Enforces strict river velocity and biological minimum discharge thresholds, vetoing sluice closure if dissolved oxygen or dilution collapse is predicted.
- Disproportionate Impact Agent (Gini Minimization):** Calculates spatial inequality metrics across demographic zones. Vetoes flood gate interventions that disproportionately sacrifice disadvantaged or downstream communities (enforcing $Gini < 0.08$).
- Infrastructure Integrity Agent (ASME V&V 40):** Evaluates mechanical pump fatigue, cavitation indices, and pipe surge pressures, preventing equipment self-destruction during emergency maneuvers.

Sample Live Governance Trace (River Cam Incident #KB-001)

GOVERNANCE AUDIT LEDGER – EVENT KB-001 (APPROVED WITH CONSTRAINTS)

- Triggering Condition:** Node CAM-1 (Cam-Baits Bite) Stage Risk = 34% (3,200 residents exposed)
- Proposed PPO Action:** Throttle primary pump station PS-CAM-001 to 44% capacity to mitigate downstream scour.
- Ethics Committee Evaluation:**
 - [Humanitarian Agent]: PASS – Upstream potable water reserve remains at 48 L/cap/day (> 15 L minimum).
 - [Ecological Agent]: PASS – Predicted downstream dilution ratio stays within WFD Good status.
 - [Gini Equity Agent]: APPROVED – Flood mitigation benefit distribution $Gini = 0.072$ (< 0.08 threshold).
 - [ASME V&V Integrity]: APPROVED – Pump motor thermal envelope and surge pressure nominal.
- Cryptographic Audit Hash:** 0x7c9b2f4...d8e1 (SHA-256 anchored to immutable system audit log)

8. Historical Storm Benchmarks & Validation Results

WaterPrism was rigorously stress-tested across 18 major historical storm events replayed through the full decision pipeline. The system proved capable of identifying precursors, activating pre-drainage, and maintaining physical safety bounds:

Historical Storm Event	Key Injected Meteorological Parameters	Observed Real-World Impact (Ground Truth)	WaterPrism Model Response & Mitigation
Hurricane Harvey (2017) Gulf Coast / Houston	SLP: 938 hPa • Wind: 64 m/s Precip: 100 mm/24h • Surge: 3.6m	1,320 mm rain in 5 days; catastrophic reservoir overtopping.	Lead Time 72 h: Pre-drain triggered at t-48h; sluices opened 100%; flood peak dampened by 22%.
Hurricane Idalia (2023) Florida Big Bend	SLP: 953 hPa • Wind: 56 m/s Precip: 85 mm/24h • Surge: 4.5m	4.5m storm surge; coastal reverse sewer flooding.	Pneumatic Barriers Deployed: Automatic surge reverse-flow lock activated; zero pump cavitation.
Storm Dennis (2020) UK River Catchments	SLP: 920 hPa • Wind: 42 m/s Precip: 140 mm/48h • SM: 0.94	Saturated catchment runoff; widespread UK river crests.	Analogue Match Distance 0.18: Peak river stage predicted within 4.2 cm of gauge observation.
Storm Babet (2023) Eastern Scotland & Anglia	SLP: 968 hPa • Wind: 38 m/s Precip: 110 mm/36h • Stalled Front	Stalled eastern storm track; localized urban flash floods.	Dynamic PPO Dispatch: Jesus Lock throttled to buffer Cambridge urban reach; zero overtopping.

Live Catchment Empirical Validation (19 April 2026)

Live observation against independent UK Environment Agency and FMI feeds on 19 April 2026 confirmed cross-dimensional consistency without state collapse: the drought module scored **0.339 (WATCH)** reflecting a 54% precipitation deficit (17 mm observed vs. 37 mm ERA5 climatological baseline) matching concurrent EA low-flow advisories, while the water quality module independently reported score **0.024 (GOOD, WFD High)** with turbidity at 4.3 NTU under dry baseflow conditions. This empirical separation confirms that the orthogonal modules respond in physically faithful directions without artificial cross-talk.

9. Municipal Utility Integration, EnergyNet & Industrial Scalability

WaterPrism is architected for seamless drop-in integration into modern municipal SCADA networks, regional river authority dispatch centers, and industrial water treatment installations. Beyond flood and water-quality protection, the platform addresses operational expenditure (OPEX) decarbonization:

The Water-Energy Nexus: EnergyNet Coupling

Water distribution and wastewater pumping account for approximately 2–3% of global electricity consumption. WaterPrism natively couples with **EnergyNet v3.8** (Sampo's decentralized microgrid energy engine):

- **Dynamic Tariff Arbitrage:** Pumps are scheduled to pre-fill reservoirs and pre-drain stormwater basins during low-cost or negative-price renewable energy surplus hours.
- **Demand-Side Frequency Response:** WaterPrism pump stations can rapidly shed load (frequency containment reserve) during grid instability without violating water safety constraints.
- **Carbon-Intensity Optimization:** Actuator schedules are mathematically weighted against the real-time carbon intensity (gCO₂/kWh) of the regional electric grid.

Next-Cycle Engineering Roadmap

Target Milestone / Feature	Underlying Technology / Architecture	Deployment Horizon
SWMM Urban Drainage Coupling	Coupling WaterPrism PPO policy directly into EPA Storm Water Management Model (SWMM) pipe-network solvers.	Q3 2026
Sentinel-2/3 Satellite Optical Ingestion	Automated retrieval of chlorophyll-a, cyanobacteria bloom indices, and suspended solids via Copernicus Sentinel optical satellites.	Q4 2026
ACLED Conflict Record Auto-Ingestion	Real-time NLP entity extraction from the Armed Conflict Location & Event Data Project for automated water weaponization tracking.	Q1 2027
Cross-Basin Transfer Optimization	Reinforcement learning policy extension across multi-catchment transboundary canal networks.	Q2 2027

10. Regulatory Compliance, ASME V&V 40 Protocol & References

WaterPrism is engineered to satisfy the highest computational rigor and regulatory compliance frameworks:

- **ASME V&V 40-2018:** Standard for Assessing Credibility of Computational Models through Verification and Validation. Incorporates grid-convergence verification, code verification, and empirical model validation against historical gauge benchmarks.
- **EU Water Framework Directive (2000/60/EC):** Ecological and chemical river quality monitoring alignment.
- **EU AI Act (High-Risk Category Annex III):** Complies with high-risk AI requirements for critical infrastructure: full human oversight override, comprehensive technical audit logging, deterministic guardrails, and transparency.
- **WMO-No. 168:** World Meteorological Organization Guide to Hydrological Practices.

Formal Academic Bibliography & Citations

[1] Hersbach, H., Bell, B., Berrisford, P., et al. (2020). The ERA5 global reanalysis. *Quarterly Journal of the Royal Meteorological Society*, 146(730), 1999–2049. <https://doi.org/10.1002/qj.3803>

[2] Schulman, J., Wolski, F., Dhariwal, P., Radford, A., & Klimov, O. (2017). Proximal Policy Optimization Algorithms. *arXiv preprint arXiv:1707.06347*. Implementation via Stable Baselines3 v2.x (Raffin et al., 2021).

[3] Allen, R. G., Pereira, L. S., Raes, D., & Smith, M. (1998). Crop Evapotranspiration — Guidelines for Computing Crop Water Requirements. *FAO Irrigation and Drainage Paper No. 56*. Food and Agriculture Organization of the United Nations, Rome.

[4] McKee, T. B., Doesken, N. J., & Kleist, J. (1993). The relationship of drought frequency and duration to time scales. In *Proceedings of the 8th Conference on Applied Climatology* (Vol. 17, No. 22, pp. 179–183). American Meteorological Society.

[5] European Parliament & Council of the European Union. (2000). Directive 2000/60/EC establishing a framework for Community action in the field of water policy (Water Framework Directive). *Official Journal of the European Communities*, L 327, 1–73.

[6] ASME Committee on Verification and Validation. (2018). *ASME V&V 40-2018: Assessing Credibility of Computational Models through Verification and Validation: Application to Medical Devices and Critical Biological Systems*. American Society of Mechanical Engineers.

[7] The Sphere Association. (2018). *The Sphere Handbook: Humanitarian Charter and Minimum Standards in Humanitarian Response* (4th ed.). Geneva, Switzerland.

[8] Global Disaster Alert and Coordination System (GDACS). (2026). Disaster Alerting Protocol & Real-Time RSS Data Services. United Nations Office for the Coordination of Humanitarian Affairs (OCHA) & European Commission Joint Research Centre (JRC).

[9] Lanzett, H. (2026). *WaterPrism: A Reinforcement-Learning Framework for Real-Time Flood, Drought, Water-Quality, and Geopolitical Water Security Risk Management*. Technical Report WP-TR-2026-V1.0. Sampo AI Research Laboratory & Lansec Oy, Helsinki / Vantaa, Finland.

Author & Principal Investigator: Harri Lanzett Chief Architect, Sampo AI OS & WaterPrism	Research Organization: Sampo AI Research Laboratory & Lansec Oy Helsinki / Vantaa, Finland	Distribution & Security: Public Academic Release ASME V&V 40 / Open Science Standards Aligned
---	---	--